



DIVER CONSOLIDATED INDUSTRIES

PROPRIETOR DIVER METAL PRODUCTS PTY. LTD

Specifications of SheetHot Extreme™ XT-Ultimate

Appearance/ Description	Multi layer composite material Multi-directional dimpled	
Temperature Range		
Minimum Continuous	-60°C	
Maximum Continuous	1100°C	
Melting Point	1200°C	
Thickness	1.4mm Nominal	
Weight	1.4 kg/m ²	
Flexibility	Great	
Flammability Rating	Non Flammable	
Ignition Temperature (flash point)	No potential for ignition	
RoHS	Yes	
Halogen Free	Yes	
Toxicity	Nil	
Binders	No	
Thermal Performance (Static)	Temperature Before (°C)	Temperature After (°C)
	100	29.6
	125	33.0
	150	36.2
	175	39.5
	200	42.6
	225	46.4
	250	50.3
	275	54.2
	300	61.9
	325	70.0

This data sheet and contained specifications exists solely for the user to determine the suitability of this product for specific use. The contents contained are derived from DCI testing procedures and Diver Metal Products PTY. LTD. makes no warranties as to their accuracy or completeness. Diver Metal Products PTY. LTD. will not be liable for any consequential or other damages arising from use or miss-use of their products



THERMAL & ACOUSTIC PRODUCTS DIVISION
MANUFACTURERS OF HEAT AND NOISE MANAGEMENT PRODUCTS,
THERMAL AND ACOUSTICS SHIELDS
45 TRAWALLA AVENUE, THOMASTOWN, VICTORIA 3074
Nat Ph: (03) 9357 2511 Nat Fax: (03) 9359 2191
Inter Ph: 61 3 9359 2191 Inter Fax: 61 3 9359 2191

